

CARACTERISTICAS TECNICAS

ARTICULO / ARTICLE :

DIAMANTE PVC

| | | | |
|--|-------------------------------------|------------------------|-----------------|
| COMPOSICION / COMPOSITION : | TEJIDO BASE : BASE FABRIC | POLIAMIDA | |
| | RECUBRIMIENTO : BACKING | PVC | |
| PESO / WEIGHT : | 450,00 GR.M2 +- 5 % | ANCHO / WIDTH : | 150 CMS. |
| PASADAS DE HILO / NUMBER OF THREADS /CM : | URDIMBRE : WARP | 8,5 - PA. 940 | |
| | TRAMA : WEFT | 8,5 - PA. 940 | |

| | |
|---|--------------------------------------|
| RESISTENCIA AL DESGARRO / RIPPING STRENGTH : (UNE EN ISO 2.411) | URDIMBRE : WARP |
| | TRAMA : WEFT |
| RESISTENCIA A LA TRACCION / BREAKING STRENGTH : (UNE EN ISO 1.421) | URDIMBRE : WARP |
| | TRAMA : WEFT |
| HIDROFUGO / HYDROPHOPIC : | NO |
| COLUMNA DE AGUA / WATER PRESSURE : (UNE EN ISO 20.811) | |
| SOLIDEZ AL FROTE / RUBBING FASTNESS : (UNE – EN ISO 105 –X12 : 1.996) | EN SECO : IN DRY STATE |
| | EN HUMEDO : IN HUMID STATE |
| SOLIDEZ A LA LUZ / COLOUR FASTNESS TO LIGHT : (UNE – EN ISO 105 – B02 : 2.001 METODO 2) | |
| ABRASION / ABRASION : (BS 3.424 (PARTE 24) | |